

# Trenchard - LPS 1175 SR3

## Specification

- Certified security to LPS 1175 Issue 6 SR3
- Single leaf configuration
- Outward opening
- Multi-point locking system
- Panic exit with ASSA ABLOY specified hardware
- Drill resistant cylinder, thumbturn and escutcheon
- Heavy-duty stainless steel dog bolt hinges
- High security dog bolt pins
- Fire rating available up to FD60



## Standards



- LPS 1175 Issue 6
- Upgradable to BSEN 1634-1: 2008
- BSEN ISO 140 Part 3

## Applications



Government  
buildings



Industrial  
units



Leisure



Public  
facilities



Transport  
hubs



Power  
generation



Healthcare



Education



Utilities



Museums  
and art

## Technical Data

- Typical insulation value: 2.5 W/m<sup>2</sup>k
- Heavy-duty stainless steel dog bolt hinges provide resistance to attack
- Seperate heavy-duty dog pins provide additional resistance to attack
- Minimum size available: 760mm W x 1800mm H
- Maximum size available: 1200mm W x 2400mm H

## Door Leaf and Frame

- Door leaves manufactured from laminated solid hardwood
- Doors are internally reinforced to provide protection against physical attack such as impact and cutting
- Doors are complete with heavy-duty hardware reinforcements
- Door edges are bevelled for ease of operation and close fit
- Doors are fitted with heavy-duty hinges and include heavy-duty security dog bolt pins for extra protection
- Door leaf thickness - 59mm
- Acoustic rating - up to 34dB with seals
- Type of veneer - When required frame material will be used to match veneer type, except when Ash is specified on Fire rated doors